





350 mA TENSIONE DI RETE - CORRENTE COSTANTE / 350 mA MAIN VOLTAGE - CONSTANT CURRENT

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	N° Min - Max LED	Rif. schema Scheme diagram
	PSU.0026.0	220÷240V 50/60Hz	80g 125x38x23 mm	IP20 - CE SELV - CLII	1-17 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1
	PSU.0027.0	220÷240V 50/60Hz	50g 75x39x22,5 mm	IP20 - CE - ENEC SELV - CLII	1-9 Power LED 1-2 High Power LED	A1
	PSU.0023.0	110÷264V 50/60Hz	100g 77x40x29 mm	IP42 - CE SELV - CLII - UR	5-15 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1
	PSU.0024.0	110÷264V 50/60Hz	220g 118x35x26 mm	IP67 - CE CLII - UR	4-15 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1
	PSU.0025.0	220÷240V 50/60Hz	80g 85x39x19 mm	IP67 - CE SELV - CLII	1-12 Power LED 1-3 High Power LED 1 COB LED 9,5 W	A1/B1

350/500 mA MULTI CORRENTE-TENSIONE / 350/500 mA MULTI CURRENT-VOLTAGE

	PSU.0030.0	100÷240V 50/60Hz	108g 110x52x22 mm	CE - IP20 KEMA KEUR SELV - cURus	DALI @ 350 mA: Max 13 Power LED Max 3 High power LED 1 COB LED 9,5 W @ 500 mA: Max 13 Power LED Max 3 High power LED 1 COB LED 14 W	A1/B1/C1/D1/ E1/F1/G1/H1/I1/ J1/K1/L1/M1/N1/ O1/P1
	PSU.0001.0	100÷240V 50/60Hz	124g 103x67x21 mm	CE - IP20 KEMA KEUR SELV - UR	1-10 DIMMER & push button @ 350 mA: Max 15 Power LED Max 3 High power LED 1 COB LED 9,5 W @ 500 mA: Max 10 Power LED Max 2 High power LED 1 COB LED 14 W	A1/B1/C1/D1/ E1/F1/G1/H1/I1/ J1/K1/L1/M1/N1/ O1/P1

500 mA TENSIONE DI RETE - CORRENTE COSTANTE / 500 mA MAIN VOLTAGE - CONSTANT CURRENT

	PSU.0003.0	100÷240V 50/60Hz	35g 51x31x21 mm	IP20 - CE KEMA KEUR SELV	1-3 Power LED 1 High Power LED	A1
	PSU.0004.0	110÷240V 50/60Hz	106g 111x38x28 mm	IP20 - CE ENEC SELV	1-8 Power LED 1 High Power LED	A1
	PSU.0022.0	220÷240V 50/60Hz	80g 125x38x23 mm	IP20 - CE SELV - CLII	10-18 Power LED 3-4 High Power LED 1 COB LED 14W/20W	A1/B1
	PSU.0002.0	100÷240V 50/60Hz	59g 52x30x23 mm	IP66 - CE SELV - CLII cURus	2-3 Power LED	A1
	PSU.0028.0	110÷264V 50/60Hz	220g 118x35x26 mm	IP67 - CE SELV - CLII cURus	3-10 Power LED 1-2 High Power LED 1 COB LED 14 W	A1/B1
	PSU.0034.0	110÷305V 50/60Hz	360g 148x40x32 mm	IP67 - CE ENEC - UR CLII - SELV	10-15 Power LED 3 High Power LED 1 COB LED 14W-20W	A1/B1