






1 W 350 mA Controllo di corrente / 1 W 350 mA Current controller

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	N° Min - Max LED	Rif. schema Scheme diagram
	ECG.0012.0	24Vdc	10g Ø12x65 mm	CE - IP65 SELV	Min 1 - Max 5 Power LED max 1 High power LED dimmerabile <i>dimnable</i>	E1

1,5 W 500 mA Controllo di corrente / 1,5 W 500 mA Current controller

	ECG.0014.0	24Vdc	10g Ø12x65 mm	CE - IP65 SELV	Min 1 - Max 5 Power LED max 1 High power LED dimmerabile <i>dimnable</i>	E1
--	-------------------	-------	------------------	-------------------	---	----

Inverter per elettroluminescenza / Electroluminescence inverter

	PSU.0031.0	230V 5W 50Hz	20g 130xØ15 mm	CE - IP20	Max 2 m	Q1
	PSU.0032.0	230V 45W 50Hz	230g 140x70x39 mm	CE - IP20	Min 20 m - Max 40 m	Q1
	PSU.0033.0	230V 300W 50Hz	2600g 240x170x76 mm	CE - IP20	Min 200 m - Max 360 m	Q1

Nota:
Distanza massima tra inverter e modulo elettroluminescenza pari a 50m, con cavo da 2x1,5mm², consumo strisce elettroluminescenti pari a 0,017W/cm².

Note:
Maximum distance between inverter and electroluminescence module equal to 50m, with cable 2x1,5mm², electroluminescence strips consumption equal to 0,017W/sqcm.