







TENSIONE DI RETE - TENSIONE COSTANTE 24 Vdc / MAIN VOLTAGE - CONSTANT LOW VOLTAGE 24 Vdc

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	Rif. schema Scheme diagram
	PSU.0006.0	110÷264V 60W 50/60Hz	410 g (14.46 oz) 182x62x35 mm (7,165x2,44x1,377 in)	IP20 - CE UR - SELV	C1/I1/R1
	PSU.0017.0	220÷240V 150W 50/60Hz	320 g (11.28 oz) 240x61x49 mm (9,448x2,401x1,929 in)	IP20 - CE KEMA KEUR SELV	C1/I1/R1
	PSU.0016.0	110÷305V 60W 50/60Hz	440 g (15.52 oz) 162,5x42,5x32 mm (6,397x1,673x1,259 in)	IP67 - CE UR - SELV	C1/I1/R1
	PSU.0010.0	110÷295V 150W 50/60Hz	1000 g (35.27 oz) 222x68x39 mm (8,74x2,677x1,535 in)	IP67 - CE UR - SELV	C1/I1/R1
	PSU.0011.0	110÷305V 240W 50/60Hz	1300 g (45.85 oz) 244x68x39 mm (9,606x2,677x1,535 in)	IP67 - CE UR - SELV	C1/I1/R1




350 mA TENSIONE DI RETE - CORRENTE COSTANTE / 350 mA MAIN VOLTAGE - CONSTANT CURRENT

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	N° Min - Max LED	Rif. schema Scheme diagram
	PSU.0025.0	220÷240V 50/60Hz	80 g (2.82 oz) 85x39x19 mm (3,346x1,535x0,748 in)	IP67 - CE SELV - CLII	1-12 Power LED 1-3 High Power LED 1 COB LED 9,5 W	A1/B1
	PSU.0023.0	110÷264V 50/60Hz	100 g (3.52 oz) 77x40x29 mm (3,031x1,574x1,141 in)	IP42 - CE SELV - CLII - UR	5-15 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1

350/500 mA MULTI CORRENTE-TENSIONE DALI / 350/500 mA MULTI CURRENT-VOLTAGE DALI

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	N° Min - Max LED	Rif. schema Scheme diagram
	PSU.0030.0	100÷240V 50/60Hz	108 g (3.8 oz) 110x52x22 mm (4,33x2,047x0,866 in)	CE - IP20 KEMA KEUR SELV - cURus	DALI @350 mA: Max 13 Power LED Max 3 High power LED 1 COB LED 9,5 W @500 mA: Max 13 Power LED Max 3 High power LED 1 COB LED 14 W	A1/B1

500 mA TENSIONE DI RETE - CORRENTE COSTANTE / 500 mA MAIN VOLTAGE - CONSTANT CURRENT

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	N° Min - Max LED	Rif. schema Scheme diagram
	PSU.0022.0	220÷240V 50/60Hz	80 g (2.82 oz) 125x38x23 mm (4,921x1,496x0,905 in)	IP20 - CE SELV - CLII	10-18 Power LED 3-4 High Power LED 1 COB LED 14/20 W	A1/B1
	PSU.0028.0	110÷264V 50/60Hz	220 g (7.76 oz) 118x35x26 mm (4,645x1,377x1,023 in)	IP67 - CE SELV - CLII cURus	3-10 Power LED 1-2 High Power LED 1 COB LED 14 W	A1/B1
	PSU.0034.0	110÷305V 50/60Hz	360 g (12.69 oz) 148x40x32 mm (5,826x1,574x1,259 in)	IP67 - CE ENEC - UR CLII - SELV	10-15 Power LED 3 High Power LED 1 COB LED 14W-20W	A1/B1