




SEQUENCER - INTERFACCIA DMX / SEQUENCER - DMX INTERFACE

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	Segnale di uscita Exit signal	Rif. schema Scheme diagram
	ECG.0011.0	24Vdc	100 g (3.52 oz) 110x36,5x62,5 mm (4,33x1,437x2,46 in) guida DIN / DIN rail	CE	3 canali 1A tensione costante dimmerabile 4 metri x canale bianco 4 metri x RGB 3 channels 1A constant voltage dimmmable 4 meters x white channel 4 meters for RGB	I1/R1


CENTRALINA DMX / DMX CONTROL GEAR

	ECG.0001.0	110÷240Vac 50/60Hz	125 g (4.4 oz) 80x90x40 mm (3,149x3,543x1,574 in)	CE	512 indirizzi 512 addresses	I1/R1
---	-------------------	-----------------------	---	----	--------------------------------	-------







INTERFACCIA DMX TENSIONE COSTANTE / DMX INTERFACE CONSTANT VOLTAGE

	ECG.0034.0	24 Vdc	175 g (6.17 oz) 178x48x33 mm (7,007x1,889x1,299 in)	CE	3 canali 6 A (432 W totali) tensione costante dimmerabile 3 channels 6 A (432 W total) constant voltage dimmmable	I1/R1
---	-------------------	--------	---	----	--	-------

INTERFACCIA DALI TENSIONE COSTANTE / DALI INTERFACE CONSTANT VOLTAGE

	ECG.0035.0	24 Vdc	150 g (5.29 oz) 120x30x22 mm (4,724x1,181x0,866 in)	CE	3 canali 5 A (360 W totali) tensione costante dimmerabile 3 channels 5 A (360 W total) constant voltage dimmmable	I1/R1
--	-------------------	--------	---	----	--	-------

ACCESSORI / ACCESSORIES

	Codice Code	Nome Name	Dimensioni Dimensions	Materiale Material	Note Notes
	ACC.0105.0	Morsettierra stagna - 2 vie Watertight thermal block 2 channels 3 poli / 3 poles	Ø 26,5x115 mm (Ø 1,043x4,527 in)	PA66	Per cavo max For cable max Ø 5÷13 mm (Ø 0,196÷0,511 in)
	ACC.0106.0	Morsettierra stagna - 2 vie Watertight thermal block 2 channels 5 poli / 5 poles	Ø 32x130 mm (Ø 1,259x5,118 in)	PA66	Per cavo max For cable max Ø 8÷17 mm (Ø 0,196÷0,511 in)
	ACC.0100.0	Muffola gel IP68 - 2 vie Waterproof connection box with gel IP68 - 2 channels 6 poli / 6 poles	59x22x22 mm (2,322x0,866x0,866 in)	Nylon PA-66	Per cavo max For cable max Ø 4÷7 mm (Ø 0,157÷0,275 in)
	ACC.0107.0	Connettore a 2 vie IP65/IP67 Waterproof connection box IP65/IP67 - 2 channels	37x12x12 mm (1,456x0,472x0,472 in)	Polycarbonato Polycarbonate	Per cavo max For cable max 0.75 mm² Ø 5,6÷7,4 mm (Ø 0,22÷0,291 in)
	ACC.0005.0	Muffola gel IP67 - 4 vie Waterproof connection box with gel IP67 - 4 channels 3 poli / 3 poles	138x31x12 mm (5,433x1,22x0,472 in)	Nylon PA-66	Per cavo max For cable max Ø 4÷8,5 mm (Ø 0,157÷0,334 in)
	ACC.0147.0	Muffola gel IP67 - 4 vie Waterproof connection box with gel IP67 - 4 channels 5 poli / 5 poles	138x31x12 mm (5,433x1,22x0,472 in)	Nylon PA-66	Per cavo max For cable max Ø 4÷8,5 mm (Ø 0,157÷0,334 in)