








TENSIONE DI RETE - TENSIONE COSTANTE 24 Vdc / MAIN VOLTAGE - CONSTANT LOW VOLTAGE 24 Vdc

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	Rif. schema Scheme diagram
	PSU.0005.0	110÷264V 30W 50/60Hz	200g (7.05 oz) 160x46x30 mm (6,299x1,811x1,181 in)	IP20 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0006.0	110÷264V 60W 50/60Hz	410g (14.46 oz) 182x62x35 mm (7,165x2,44x1,377 in)	IP20 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0020.0	220÷240V 70W 50/60Hz	290g (10.22 oz) 225x60x36 mm (8,858x2,362x1,417 in)	IP20 - CE KEMA KEUR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0007.0	110÷264V 96W 50/60Hz	520g (18.34 oz) 201x71x35 mm (7,913x2,795x1,377 in)	IP20 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0012.0	110÷264V 120W 50/60Hz	650g (22.92 oz) 125x114x40 mm (4,921x4,488x1,574 in) guida DIN / DIN rail	IP20 - CE UL - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0017.0	220÷240V 150W 50/60Hz	320g (11.28 oz) 240x61x49 mm (9,448x2,401x1,929 in)	IP20 - CE KEMA KEUR SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0013.0	110÷264V 240W 50/60Hz	1030g (36.33 oz) 125x114x63 mm (4,921x4,488x2,48 in) guida DIN / DIN rail	IP20 - CE UL - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0014.0	110÷264V 480W 50/60Hz	1600g (56.43 oz) 125x129x86 mm (4,921x5,078x3,385 in) guida DIN / DIN rail	IP20 - CE UL - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0021.0	110÷305V 320W 50/60Hz	1900g (67.02 oz) 252x90x44 mm (9,921x3,543x1,732 in)	IP65 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0008.0	110÷264V 20W 50/60Hz	220g (7.76 oz) 118x35x26 mm (4,645x1,377x1,023 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0015.0	110÷305V 40W 50/60Hz	440g (15.52 oz) 162,5x42,5x32 mm (6,397x1,673x1,259 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0016.0	110÷305V 60W 50/60Hz	440g (15.52 oz) 162,5x42,5x32 mm (6,397x1,673x1,259 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0009.0	110÷295V 96W 50/60Hz	1000g (35.27 oz) 222x68x39 mm (8,74x2,677x1,535 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0010.0	110÷295V 150W 50/60Hz	1000g (35.27 oz) 222x68x39 mm (8,74x2,677x1,535 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0018.0	220÷240V 150W 50/60Hz	600g (21.16 oz) 225x65x51 mm (8,858x2,559x2,007 in)	IP67 - CE KEMA KEUR SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0011.0	110÷305V 240W 50/60Hz	1300g (45.85 oz) 244x68x39 mm (9,606x2,677x1,535 in)	IP67 - CE UR - SELV	C1/D1/E1/F1/G1/ H1/I1/J1/K1/L1/ M1/N1/O1/P1


350 mA TENSIONE DI RETE - CORRENTE COSTANTE / 350 mA MAIN VOLTAGE - CONSTANT CURRENT

	Codice Code	Voltaggio Voltage	Peso e dimensioni Weight and dimensions	Omologazioni Homologation	N° Min - Max LED	Rif. schema Scheme diagram
	PSU.0026.0	220÷240V 50/60Hz	80g (2.82 oz) 125x38x23 mm (4,921x1,496x0,905 in)	IP20 - CE SELV - CLII	1-17 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1
	PSU.0027.0	220÷240V 50/60Hz	50g (1.76 oz) 75x39x22,5 mm (2,952x1,535x0,885 in)	IP20 - CE - ENEC SELV - CLII	1-9 Power LED 1-2 High Power LED	A1
	PSU.0023.0	110÷264V 50/60Hz	100g (3.52 oz) 77x40x29 mm (3,031x1,574x1,141 in)	IP42 - CE SELV - CLII - UR	5-15 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1
	PSU.0024.0	110÷264V 50/60Hz	220g (7.76 oz) 118x35x26 mm (4,645x1,377x1,023 in)	IP67 - CE CLII - UR	4-15 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1
	PSU.0025.0	220÷240V 50/60Hz	80g (2.82 oz) 85x39x19 mm (3,346x1,535x0,748 in)	IP67 - CE SELV - CLII	1-12 Power LED 1-3 High Power LED 1 COB LED 9,5 W	A1/B1

350/500 mA MULTI CORRENTE-TENSIONE / 350/500 mA MULTI CURRENT-VOLTAGE

	PSU.0030.0	100÷240V 50/60Hz	108g (3.80 oz) 110x52x22 mm (4,332x2,047x0,866 in)	CE - IP20 KEMA KEUR SELV - cURus	DALI @ 350 mA: Max 13 Power LED Max 3 High power LED 1 COB LED 9,5 W @ 500 mA: Max 13 Power LED Max 3 High power LED 1 COB LED 14 W	A1/B1/C1/D1/ E1/F1/G1/H1/ I1/J1/K1/L1/M1/ N1/O1/P1
	PSU.0001.0	100÷240V 50/60Hz	124g (4.37 oz) 103x67x21 mm (4,055x2,637x0,826 in)	CE - IP20 KEMA KEUR SELV - UR	1-10 DIMMER & push button @ 350 mA: Max 15 Power LED Max 3 High power LED 1 COB LED 9,5 W @ 500 mA: Max 10 Power LED Max 2 High power LED 1 COB LED 14 W	A1/B1/C1/D1/ E1/F1/G1/H1/ I1/J1/K1/L1/M1/ N1/O1/P1

500 mA TENSIONE DI RETE - CORRENTE COSTANTE / 500 mA MAIN VOLTAGE - CONSTANT CURRENT

	PSU.0003.0	100÷240V 50/60Hz	35g (1.23 oz) 51x31x21 mm (2,007x1,22x0,826 in)	IP20 - CE KEMA KEUR SELV	1-3 Power LED 1 High Power LED	A1
	PSU.0004.0	110÷240V 50/60Hz	106g (3.73 oz) 111x38x28 mm (4,37x1,496x1,102 in)	IP20 - CE ENEC SELV	1-8 Power LED 1 High Power LED	A1
	PSU.0022.0	220÷240V 50/60Hz	80g (2.82 oz) 125x38x23 mm (4,921x1,496x0,905 in)	IP20 - CE SELV - CLII	10-18 Power LED 3-4 High Power LED 1 COB LED 14W/20W	A1/B1
	PSU.0002.0	100÷240V 50/60Hz	59g (2.08 oz) 52x30x23 mm (2,047x1,181x0,905 in)	IP66 - CE SELV - CLII cURus	2-3 Power LED	A1
	PSU.0028.0	110÷264V 50/60Hz	220g (7.76 oz) 118x35x26 mm (4,645x1,377x1,023 in)	IP67 - CE SELV - CLII cURus	3-10 Power LED 1-2 High Power LED 1 COB LED 14 W	A1/B1
	PSU.0034.0	110÷305V 50/60Hz	360g (12.69 oz) 148x40x32 mm (5,826x1,574x1,259 in)	IP67 - CE ENEC - UR CLII - SELV	10-15 Power LED 3 High Power LED 1 COB LED 14W-20W	A1/B1